# **Envidas-510MB**

## 4U Rackmount Chassis with Front USB and PS/2 Interfaces




#### **Features**

- Supports either an ATX motherboard or a backplane with up to 14 slots
- Equipped with 250/300 W ATX PFC PS/2 power supply
- Easy to install front-accessible drive bays to hold three 5.25" and two 3.5" disk drives
- ❖ Front-accessible USB & PS/2 interfaces
- Designed to withstand environmental extremes, such as shock, vibration and high temperature

#### Introduction

The EnviDAS-510 is a 19" rack mount industrial computer chassis for mission-critical applications. This unit can accommodate a 14-slot PCI/ISA bus passive backplane or a standard ATX mother-board and supports versatile power supplies. A lockable door in the front secures the unit from any unauthorized access. One hot-swap filtered cooling fan maintains positive air circulation through the whole chassis. With its hold-down clamp and shock mounted drive brackets, the EnviDAS-510 can withstand shock, vibration and dust found in harsh environments.







Motherboard can fit in 450 mm (17.7") depth



## Envitech Europe

PO Box: 22979 Glasgow G67 9DY

Tel.: +44(0)141 416 2099, Fax: +44(0)141 404 2545


Email: info@envitech-europe.co.uk Web Site: http://envitech-europe.co.uk


# IPC-510MB


### **Specifications**


| Issue         | Sub-Issue              | Front Accessible  | Internal      |
|---------------|------------------------|---|---------------|
| Drive Bay     | 3.5"                   | 1   | 1             |
|               | 5.25"                  | 3   |               |
| Cooling       | Fan                    | 1 (77 CFM/each)   |               |
| I/O Interface | USB                    | 2   |               |
|               | PS/2                   | 1   |               |
| Miscellaneous | Rear panel Indicator   | BP version: Two D-SUB 9-pin openings                              |               |
|               |                        | MB version: One D-SUB 9-pin bracket and one 68 -pin SCSI openings |               |
|               |                        | LED display for power on and HDD activity                         |               |
| Environment   |                        | Operating   | Non-Operating |
|               | Temperature            | 0 ~ 40° C   | -20 ~ 60° C   |
|               | Humidity               | 1-~85%  | 10~95%        |
|               | Vibration (5-500 Hz)   | 1 Grms  | 2 G           |
|               | Sock                   | 10 G (With 11 msec duration,1/2 sine wave)                        | 30 G          |
|               | Altitude               | 10,000 ft   | 40,000 ft     |
|               | Acoustic Noise         | Less than 52dB sound pressure at 5 ~ 28° C                        |               |
|               | Dimensions (W x H x D) | 482x 177 x 448 mm (19" x 7" x 17.6")                              |               |
| Physical      | Weight                 | 12.5kg (27.5 lb)  |               |
| Compliance    | Safety                 | CE compliant  |               |

#### **Dimensions**











## Envitech Europe

PO Box: 22979 Glasgow G67 9DY

Tel.: +44(0)141 416 2099, Fax: +44(0)141 404 2545

Email: info@envitech-europe.co.uk Web Site: http://envitech-europe.co.uk